

3-PHASE ELECTRONIC MOTOR CONTACTOR

REVERSING CONTACTOR





Dimensions for the 45 mm module (LAS1/LAW/LAK15A/LAD/LAA 30A)




SCHRACK-INFO

- Electronic contactor for reverse motor control
- Rated operating current up to 10 A AC-3/8 A AC-4
- Rated operating voltage up to 480V AC
- Control voltage 5-24 V DC or 24-230 V AC
- 2 separate potential-free control voltage inputs
- Meets requirements of EN 60947-4-2
- Modular design with an overall width of 45 mm on DIN rail
- LED operating status indicator
- IP 20 shock protection
- AC and DC control voltage
- Integrated interlock circuit

RATED CURRENT	RATED VOLTAGE	CONTROL VOLTAGE	DIM. (WxHxD) mm	EAN CODE	AVAILABLE	ORDER NO.
10 A	24-480 V AC 50/60 HZ	24-230 V AC/DC	45x110x124,3	5705609000264	999 0-0	LAW34102

ELECTRONIC/MOTOR CONTACTOR ACCESSORIES



DESCRIPTION	EAN CODE	AVAILABLE	ORDER NO.
Thermal overload protection	9004840150117	000	LASUP62



I KNOW WHERE TO FIND IT!

THE SCHRACK TECHNIK WEB SHOP WITH NAVIGATOR WWW.SCHRACK.COM

- Finding product information made easy
- Buying products around the clock
- Quick access customer service

Page 823



