

■ RCCB Residual Current Circuit Breaker series BCF0, 10kA, type A, version G



BC034403


■ Schrack-Info

- Sensitivity: pulse current sensitive (type A)
- 10 ms tripping delay type G
- Short-circuit strength 10kA
- Tripping independent of line voltage
- Contact position color indicator (red/green)
- Most common accessories: auxiliary contact 1 NO / 1 NC BD900002


Standards:	IEC/EN 61008	
Pole	2-pole, 4-pole	
Rated voltage U_s :	230V/240V	
2-pole	230/400 and 240/415V-AC	
4-pole		
Rated frequency:	50/60Hz	
Rated current I_n :	40A, 63A, 80A, 100A	
Tripping-type:	A (pulse current sensitive)	
Rated current $I_{\Delta n}$:	30mA	
Delay-type:	G (ÖVE/ÖNORM E 8601), at least 10ms	
Surge current proof:	>3kA (8/20 μ s) Type G	
Tripping:	line voltage-independent	
Rated insulation voltage U_i :	440V	
Rated impulse withstand voltage U_{imp} :	4kV (1.2/50 μ s)	
Rated breaking capacity I_m and rated residual making $I_{\Delta m}$:		
$I_n = 40A$	500A	
$I_n = 63A$	630A	
$I_n = 80A$	800A	
$I_n = 100A$	1000A	
Rated short-circuit capacity I_{cn} :	10kA according EN 61008	
Max. back up fuse:	overload (OPCD):	short circuit (SCPD):
$I_n = 40A$	25A gG/gL	63A gG/gL
$I_n = 63A$	40A gG/gL	63A gG/gL
$I_n = 80A$	50A gG/gL	80A gG/gL
$I_n = 100A$	63A gG/gL	100A gG/gL
back up fuse proof $I_n = 40A$ vsf.	40A gG/gL	80A gG/gL
back up fuse proof $I_n = 63A$ vsf.	63A gG/gL	80A gG/gL
Operating voltage test-circuit:	195,5 - 440V-AC	
Endurance:	> 4.000 operating cycles (mechanical > 20.000)	
Lamp strength:	max. 20 electronic ballasts per phase, max. 60 per RCCB (typical, commercially available)	
Contact position indicator:	red / green	
Rated tripping temperature:	-25°C up to +40°C	
Max. ambient temperature:		
25A	-35°C up to +55°C	
40A - 100A	-35°C up to +60°C	
Climatic proofing:	according to IEC/EN 61008	
Finger and hand touch safe:	according to BGV A3	
Degree of protection:	IP 20 (covered IP40)	
Operating position:	in any position	
Terminals:	Double clamp / lift terminal	
Terminal cross-section:	1-35 mm ² solid, 2x16 mm ² stranded	
Terminal screws:	Pozidriv PZ2	
Terminal tightening torque:	2 - 2,4 Nm	
Mounting:	on DIN rail by latching snap-on mounting	
Test interval:	Operate test button of RCCB 1 x every 6 months. The system operator is responsible for this test! Under non-household-type conditions (e.g. humid or dusty environment), it is recommended to carry out the test in monthly intervals. Pressing the test button "T" only tests the function of the residual current (RC) circuit breaker. This test does not replace the earthing resistance measurement (RE) nor the proper protective conductor test that must be performed separately.	

■ RCCB Residual Current Circuit Breaker series BCF0, 10kA, type A, version G

■ Dimensions




■ Wiring diagram



■ RCCB Residual Current Circuit Breaker series BCF0, 10kA, type A, version G

■ Tripping characteristic delayed (G)



Ambient temperature	Type											
	16A 2-pole	16A 4-pole	25A 2-pole	25A 4-pole	40A 2-pole	40A 4-pole	63A 2-pole	63A 4-pole	80A 2-pole	80A 4-pole	100A 2-pole	100A 4-pole
40°	16	16	25	25	40	40	63	63	80	80	100	100
45°	14	14	22	22	37	37	59	59	76	76	95	95
50°	11	1	19	19	33	34	55	55	72	72	90	90
55°	9	9	16	16	30	31	50	50	68	68	85	85
60°	-	-	-	-	26	27	45	45	64	64	80	80

 RCCB Residual Current Circuit Breaker series BCF0, 10kA, type A, version G

Conductor cross section [mm ²]	Number of single conductors, rigid, single-wire Cu conductors					
	1	2	3	4	5	6
1,5	+	+	+	+	+	-
2,5	+	+	+	+	-	-
4	+	+	+	+	-	-
6	+	+	+	+	-	-
10	+	+	+	-	-	-
16	+	+	-	-	-	-
25	+	-	-	-	-	-
35	+	-	-	-	-	-

Conductor cross section [mm ²]	Number of single conductors, rigid, multi-wire Cu conductors					
	1	2	3	4	5	6
10	+	+	+	-	-	-
16	+	+	-	-	-	-
25	+	-	-	-	-	-
35	+	-	-	-	-	-

Conductor cross section [mm ²]	Number of single conductors, flexible Cu conductors without sleeves					
	1	2	3	4	5	6
1,5	-	-	-	-	+	-
2,5	-	-	+	+	-	-
4	-	+	+	+	-	-
6	-	+	+	+	-	-
10	-	+	-	-	-	-
16	-	+	-	-	-	-
25	-	-	-	-	-	-
35	-	-	-	-	-	-

Conductor cross section [mm ²]	Number of single conductors, flexible Cu conductors with sleeves					
	1	2	3	4	5	6
1,5	+	-	-	-	-	-
2,5	+	-	-	-	-	-
4	+	-	-	-	-	-
6	+	-	-	-	-	-
10	+	-	-	-	-	-
16	+	-	-	-	-	-
25	+	-	-	-	-	-
35	+	-	-	-	-	-

Conductor cross section [mm ²]	Number of single conductors, flexible Cu conductors with different cross-sections, without sleeves								
	1	2	3	4	5	6	7	8	9
1,5	+	-	-	-	-	-	-	-	-
2,5	+	+	-	-	-	+	-	-	-
4	-	+	+	-	-	-	+	-	-
6	-	-	+	+	-	+	-	+	-
10	-	-	-	+	+	-	+	-	+
16	-	-	-	-	+	-	-	+	-
25	-	-	-	-	-	-	-	-	+
35	-	-	-	-	-	-	-	-	-

■ RCCB Residual Current Circuit Breaker series BCF0, 10kA, type A, version G, 30mA



BC034103

■ Schrack-Info

- Pulse current sensitive version type G/A
- Also protects in specific forms of non-smoothed DC residual currents
- Most common accessories: Auxiliary contact 1 NO / 1 NC BD900002

DESCRIPTION	AVAILABLE	ORDER NO.
2-pole		
40A / 2 / 0,03A		BC034203
4-pole		
40A / 4 / 0,03A		BC034103
40A / 4 / 0,03A back-up fuse proof		BC034403
63A / 4 / 0,03A		BC036103
80A / 4 / 0,03A		BC038103
100A / 4 / 0,03A		BC030103
63A / 4 / 0,03A back-up fuse proof		BC036603

