

POWER SUPPLY UNITS, SINGLE-PHASE DC POWER SUPPLY, OPEN DESIGN TYPE, FILTERED



LP702110I

SCHRACK-INFO

Transformer-based DC power supply with an output voltage of 24 V DC.

- Primary voltages 230 V AC, 230 – 400 V AC
- Up to 25 A output current
- Low residual ripple < 5%
- Self-cooling

DESCRIPTION	CU WEIGHT (g)	EAN CODE	AVAILABLE	ORDER NO.
230-400 V 50/60 HZ / 24 V DC				
230-400/24 V 3 A	360	9004840454574		LP702103I
230-400/24 V 5 A	790	9004840454581		LP702105I
230-400/24 V 8 A	850	9004840454598		LP702108I
230-400/24 V 10 A	1400	9004840454604		LP702110I
230-400/24 V 15 A	1400	9004840454611		LP702115I
230-400/24 V 20 A	1700	9004840154948		LP702120T
230-400/24 V 25 A	2500	9004840159073		LP702125T
230 V 50/60 Hz / 24 V DC				
230/24 V 1.5 A	260	9004840548099		LP7021B1I
230/24 V 20.0 A	2000	9004840154955		LP703120T
230/24 V 25.0 A	3000	9004840199444		LP703125T

POWER SUPPLY UNITS, THREE-PHASE POWER SUPPLY, OPEN DESIGN TYPE



LP701310T

SCHRACK-INFO

Three-phase, transformer-based DC power supply with an output voltage of 24 V DC.

- Output currents of 10 – 40 A
- Low residual ripple < 5%

DESCRIPTION	CU WEIGHT (g)	EAN CODE	AVAILABLE	ORDER NO.
400/24 V DC, 10 A	940	9004840454536		LP701310I
400/24 V DC, 15 A	1040	9004840454543		LP701315I
400/24 V DC, 20 A	1360	9004840454550		LP701320I
400/24 V DC, 30 A	1600	9004840454567		LP701330I
400/24 V DC, 40 A	3500	9004840174434		LP701340T