

Relay Sockets for MT Relays



YMR78700



YMR78701



MT78740




MTMFOW00


Schrack-Info

- DIN rail snap mounting
- Screw mounting with centering screw
- Pozidrive screws with lift terminals
- Logical arrangement of I/O terminals
- White labelling field

Dimensions (mm)



Reduction Curve




Reduction Curve

I	DC current in [A]
θ	Ambient temperature in [°C]

Relay Sockets & Sets

Relay Sockets for MT Relays

Circuit Diagrams



Time Module Functionalities



Circuit Diagrams & Time module Functionalities

#1	2 CO
#2	3 CO
#3	3-pole
A	Response delayed MTMZOW00, MTMFOW00
B	Reset delayed MTMFOW00
C	Single shot leading edge with pulse control MTMFOW00
D	Single shot trailing edge MTMFOW00
E	Response delayed with control contact MTMFOW00
F	Single shot leading edge MTMFOW00
G	Flashing pause starting MTMFOW00
H	Flashing pulse starting MTMFOW00

Relay Sockets for MT Relays


Technical Data

YMR78700, YMR78701, MT78740

Rated current		10 A
Rated voltage/ max. switching voltage		240 / 400 V
Dielectric strength	Coil-contact set	2500 V _{rms}
	Open contact	1500 V _{rms}
	Adjacent contacts	2500 V _{rms}
Clearance/ creepage	Coil contact circuit	≥ 2.8 / 4 mm
Insulation to IEC 60664-1 Type of insulation	Coil-contact set	Basic
	Open contact	Functional
	Adjacent contact	Basic
Rated insulation voltage		250 V
Pollution degree		2
Overvoltage category		III
Ambient temperature		-20...+80 °C
Degree of protection		IP20
Mounting distance		>0 dense packing
Mounting/ rail		DIN50024/ 22
Terminal capacity		2 x 2.5 mm ²
Terminal torque in according to IEC 61984		0.5 Nm
	Max.	0.7 Nm

Function Modules For Socket MT78740

Rated voltage	24...240 V DC / AC
Mains frequency	48...63 Hz
Repeat accuracy	± 0.5 %
Repeatability	≤ 0.5 % or 5 ms
Temperature influence	≤ 0.1 % pro °C
Time ranges switchable	0.05 s...240 h in 8 ranges
Ambient temperature	-25...+55 °C

DESCRIPTION	AVAILABLE	ORDER NO.
DIN rail mounted plug-in socket for MT2 relays, 8 pole, 10A (2 CO) with screw terminals, not compatible with function modules		YMR78701
DIN rail mounted plug-in socket for MT3 relays and timer relays series ZR4, 11 pole, 10A (3 CO), with screw terminals, not compatible with function modules		YMR78700
DIN rail mounted plug-in socket for MT3 relays, 11 pole, 10A (3 CO), with screw terminals, compatible with function modules		MT78740
LED module red 24V AC/DC for socket MT78740		MTML0024
Protection diode module 1N4007 for socket MT78740		MTMT00A0
RC-Network module 110-240V AC for socket MT78740		MTMU0730
Single function module Delay ON for socket MT78740		MTMZOW00
Multifunction module for socket MT78740		MTMFOW00
Metal retaining clip		MT28800



Order no. blue: on stock, usually ready for delivery on the day of order