

FRAME SIZE 1 TO 1600A – WITHOUT GUIDE FRAME



MO116235

SCHRACK INFO


Basic unit without release, factory assembled with selected components and delivered as complete device. Replacement switch for existing frames. The nominal current must be appropriate for the guide frame.

DESCRIPTION	WEIGHT (kg)	I _{CU}	TYPE	ORDER NO.
3-POLE 55 kA				
800 A	45	55 kA	MO1B-800	MO108235
1000 A	45	55 kA	MO1B-1000	MO110235
1250 A	45	50 kA	MO1B-1250	MO112235
1600 A	45	55 kA	MO1B-1600	MO116235
3-POLE 66 kA				
800 A	45	66 kA	MO1N-800	MO108335
1000 A	45	66 kA	MO1N-1000	MO110335
1250 A	45	66 kA	MO1N-1250	MO112335
1600 A	45	66 kA	MO1N-1600	MO116335
4-POLE 55 kA				
800 A	54	55 kA	MO1B-4-800	MO108245
1000 A	54	55 kA	MO1B-4-1000	MO110245
1250 A	54	55 kA	MO1B-4-1250	MO112245
1600 A	54	55 kA	MO1B-4-1600	MO116245
4-POLE 66 kA				
800 A	54	66 kA	MO1N-4-800	MO108345
1000 A	54	66 kA	MO1N-4-1000	MO110345
1250 A	54	66 kA	MO1N-4-1250	MO112345
1600 A	54	66 kA	MO1N-4-1600	MO116345
FRAME				
Guide frame for frame size 1				upon request

FRAME SIZE 1 TO 1600A – WITH GUIDE FRAME, REAR-SIDE CONNECTION, HORIZONTAL



MO116236



Connection, rear view

SCHRACK INFO


Basic unit without release, factory assembled with selected components and delivered as complete device.

DESCRIPTION	WEIGHT (kg)	I _{CU}	TYPE	ORDER NO.
3-POLE 55 kA				
800 A	70	55 kA	MO1B-800	MO108236
1000 A	70	55 kA	MO1B-1000	MO110236
1250 A	70	50 kA	MO1B-1250	MO112236
1600 A	70	55 kA	MO1B-1600	MO116236
3-POLE 66 kA				
800 A	70	66 kA	MO1N-800	MO108336
1000 A	70	66 kA	MO1N-1000	MO110336
1250 A	70	66 kA	MO1N-1250	MO112336
1600 A	70	66 kA	MO1N-1600	MO116336
4-POLE 55 kA				
800 A	84	55 kA	MO1B-4-800	MO108246
1000 A	84	55 kA	MO1B-4-1000	MO110246
1250 A	84	55 kA	MO1B-4-1250	MO112246
1600 A	84	55 kA	MO1B-4-1600	MO116246
4-POLE 66 kA				
800 A	84	66 kA	MO1N-4-800	MO108346
1000 A	84	66 kA	MO1N-4-1000	MO110346
1250 A	84	66 kA	MO1N-4-1250	MO112346
1600 A	84	66 kA	MO1N-4-1600	MO116346

FRAME SIZE 1 TO 1600A – WITH GUIDE FRAME, REAR-SIDE CONNECTION, VERTICAL



MO116236



Connection, rear view

SCHRACK INFO


Basic unit without release, factory assembled with selected components and delivered as complete device.

DESCRIPTION	WEIGHT (kg)	I _{CU}	TYPE	ORDER NO.
3-POLE 55 kA				
800 A	70	55 kA	MO1B-800	MO108237
1000 A	70	55 kA	MO1B-1000	MO110237
1250 A	70	55 kA	MO1B-1250	MO112237
1600 A	70	55 kA	MO1B-1600	MO116237
3-POLE 66 kA				
800 A	70	66 kA	MO1N-800	MO108337
1000 A	70	66 kA	MO1N-1000	MO110337
1250 A	70	66 kA	MO1N-1250	MO112337
1600 A	70	66 kA	MO1N-1600	MO116337
4-POLE 55 kA				
800 A	84	55 kA	MO1B-4-800	MO108247
1000 A	84	55 kA	MO1B-4-1000	MO110247
1250 A	84	55 kA	MO1B-4-1250	MO112247
1600 A	84	55 kA	MO1B-4-1600	MO116247
4-POLE 66 kA				
800 A	84	66 kA	MO1N-4-800	MO108347
1000 A	84	66 kA	MO1N-4-1000	MO110347
1250 A	84	66 kA	MO1N-4-1250	MO112347
1600 A	84	66 kA	MO1N-4-1600	MO116347

FRAME SIZE 1 TO 1600A – WITH GUIDE FRAME AND CONNECTING FLANGE



MO116236



Connection, rear view

SCHRACK INFO

Basic unit without release, factory assembled with selected components and delivered as complete device.

DESCRIPTION	WEIGHT (kg)	I _{CU}	TYPE	ORDER NO.
3-POLE 55 kA				
800 A	70	55 kA	MO1B-800	MO108234
1000 A	70	55 kA	MO1B-1000	MO110234
1250 A	70	55 kA	MO1B-1250	MO112234
1600 A	70	55 kA	MO1B-1600	MO116234
3-POLE 66 kA				
800 A	70	66 kA	MO1N-800	MO108334
1000 A	70	66 kA	MO1N-1000	MO110334
1250 A	70	66 kA	MO1N-1250	MO112334
1600 A	70	66 kA	MO1N-1600	MO116334
4-POLE 55 kA				
800 A	84	55 kA	MO1B-4-800	MO108244
1000 A	84	55 kA	MO1B-4-1000	MO110244
1250 A	84	55 kA	MO1B-4-1250	MO112244
1600 A	84	55 kA	MO1B-4-1600	MO116244
4-POLE 66 kA				
800 A	84	66 kA	MO1N-4-800	MO108344
1000 A	84	66 kA	MO1N-4-1000	MO110344
1250 A	84	66 kA	MO1N-4-1250	MO112344
1600 A	84	66 kA	MO1N-4-1600	MO116344

FRAME SIZE 2 TO 3200A – WITHOUT GUIDE FRAME



MO232335

SCHRACK INFO


Basic unit without release, factory assembled with selected components and delivered as complete device. Replacement switch for existing frames. The nominal current must be appropriate for the guide frame.

DESCRIPTION	WEIGHT (kg)	I _{CU}	TYPE	ORDER NO.
3-POLE 66 kA				
2000 A	60	66 kA	MO2B-2000	MO220235
2500 A	63	66 kA	MO2B-2500	MO225235
3-POLE 80 kA				
800 A	60	80 kA	MO2N-800	MO208335
1000 A	60	80 kA	MO2N-1000	MO210335
1250 A	60	80 kA	MO2N-1250	MO212335
1600 A	60	80 kA	MO2N-1600	MO216335
2000 A	60	80 kA	MO2N-2000	MO220335
2500 A	63	80 kA	MO2N-2500	MO225335
3200 A	68	80 kA	MO2N-3200	MO232335
4-POLE 66 kA				
2000 A	72	66 kA	MO2B-4-2000	MO220245
2500 A	76	66 kA	MO2B-4-2500	MO225245
4-POLE 80 kA				
800 A	72	80 kA	MO2N-4-800	MO208345
1000 A	72	80 kA	MO2N-4-1000	MO210345
1250 A	72	80 kA	MO2N-4-1250	MO212345
1600 A	72	80 kA	MO2N-4-1600	MO216345
2000 A	72	80 kA	MO2N-4-2000	MO220345
2500 A	76	80 kA	MO2N-4-2500	MO225345
3200 A	82	80 kA	MO2N-4-3200	MO232345
FRAME				
Guide frame for frame size 2				upon request

FRAME SIZE 2 TO 3200A – WITH GUIDE FRAME, REAR-SIDE CONNECTION, HORIZONTAL



MO220236



Connection, rear view

SCHRACK INFO


Basic unit without release, factory assembled with selected components and delivered as complete device.

DESCRIPTION	WEIGHT (kg)	I _{CU}	TYPE	ORDER NO.
3-POLE 66 kA				
2000 A	91	66 kA	MO2B-2000	MO220236
2500 A	102	66 kA	MO2B-2500	MO225236
3-POLE 80 kA				
800 A	91	80 kA	MO2N-800	MO208336
1000 A	91	80 kA	MO2N-1000	MO210336
1250 A	91	80 kA	MO2N-1250	MO212336
1600 A	91	80 kA	MO2N-1600	MO216336
2000 A	91	80 kA	MO2N-2000	MO220336
2500 A	102	80 kA	MO2N-2500	MO225336
3200 A	113	80 kA	MO2N-3200	MO232336
4-POLE 66 kA				
2000 A	109	66 kA	MO2B-4-2000	MO220246
2500 A	123	66 kA	MO2B-4-2500	MO225246
4-POLE 80 kA				
800 A	109	80 kA	MO2N-4-800	MO208346
1000 A	109	80 kA	MO2N-4-1000	MO210346
1250 A	109	80 kA	MO2N-4-1250	MO212346
1600 A	109	80 kA	MO2N-4-1600	MO216346
2000 A	109	80 kA	MO2N-4-2000	MO220346
2500 A	123	80 kA	MO2N-4-2500	MO225346
3200 A	136	80 kA	MO2N-4-3200	MO232346

FRAME SIZE 2 TO 3200A – WITH GUIDE FRAME, REAR-SIDE CONNECTION, VERTICAL



MO220236



Connection, rear view

SCHRACK INFO

Basic unit without release, factory assembled with selected components and delivered as complete device.


DESCRIPTION	WEIGHT (kg)	I _{CU}	TYPE	ORDER NO.
3-POLE 66 kA				
2000 A	91	66 kA	MO2B-2000	MO220237
2500 A	102	66 kA	MO2B-2500	MO225237
3-POLE 80 kA				
800 A	91	80 kA	MO2N-800	MO208337
1000 A	91	80 kA	MO2N-1000	MO210337
1250 A	91	80 kA	MO2N-1250	MO212337
1600 A	91	80 kA	MO2N-1600	MO216337
2000 A	91	80 kA	MO2N-2000	MO220337
2500 A	102	80 kA	MO2N-2500	MO225337
3200 A	113	80 kA	MO2N-3200	MO232337
4-POLE 66 kA				
2000 A	109	66 kA	MO2B-4-2000	MO220247
2500 A	123	66 kA	MO2B-4-2500	MO225247
4-POLE 80 kA				
800 A	109	80 kA	MO2N-4-800	MO208347
1000 A	109	80 kA	MO2N-4-1000	MO210347
1250 A	109	80 kA	MO2N-4-1250	MO212347
1600 A	109	80 kA	MO2N-4-1600	MO216347
2000 A	109	80 kA	MO2N-4-2000	MO220347
2500 A	123	80 kA	MO2N-4-2500	MO225347
3200 A	136	80 kA	MO2N-4-3200	MO232347

MO – FRAME SIZE 2 / WITHDRAWABLE MODELS

FRAME SIZE 2 TO 3200A – WITH GUIDE FRAME AND CONNECTING FLANGE



MO220236



ANSCHLUSS-RÜCKANSICHT

SCHRACK INFO

Basic unit without release, factory assembled with selected components and delivered as complete device.

DESCRIPTION	WEIGHT (kg)	I _{CU}	TYPE	ORDER NO.
3-POLE 66 kA				
2000 A	91	66 kA	MO2B-2000	MO220234
2500 A	102	66 kA	MO2B-2500	MO225234
3-POLE 80 kA				
800 A	91	80 kA	MO2N-800	MO208334
1000 A	91	80 kA	MO2N-1000	MO210334
1250 A	91	80 kA	MO2N-1250	MO212334
1600 A	91	80 kA	MO2N-1600	MO216334
2000 A	91	80 kA	MO2N-2000	MO220334
2500 A	102	80 kA	MO2N-2500	MO225334
3200 A	113	80 kA	MO2N-3200	MO232334
4-POLE 66 kA				
2000 A	109	66 kA	MO2B-4-2000	MO220244
2500 A	123	66 kA	MO2B-4-2500	MO225244
4-POLE 80 kA				
800 A	109	80 kA	MO2N-4-800	MO208344
1000 A	109	80 kA	MO2N-4-1000	MO210344
1250 A	109	80 kA	MO2N-4-1250	MO212344
1600 A	109	80 kA	MO2N-4-1600	MO216344
2000 A	109	80 kA	MO2N-4-2000	MO220344
2500 A	123	80 kA	MO2N-4-2500	MO225344
3200 A	136	80 kA	MO2N-4-3200	MO232344

FRAME SIZE 3 TO 6300A – WITHOUT GUIDE FRAME



MO340435

SCHRACK INFO

Basic unit without release, factory assembled with selected components and delivered as complete device. Replacement switch for existing frames. The nominal current must be appropriate for the guide frame.

DESCRIPTION	WEIGHT (kg)	I _{CU}	TYPE	ORDER NO.
3-POLE 100 kA				
4000 A	88	100 kA	MO3H-4000	MO340435
5000 A	88	100 kA	MO3H-5000	MO350435
6300 A	96	100 kA	MO3H-6300	MO363435
4-POLE 100 kA				
4000 A	106	100 kA	MO3H-4-4000	MO340445
5000 A	106	100 kA	MO3H-4-5000	MO350445
6300 A	108	100 kA	MO3H-4-6300	MO363445


FRAME

Guide frame for frame size 3	upon request
------------------------------	--------------

FRAME SIZE 3 TO 6300A – WITH GUIDE FRAME, REAR-SIDE CONNECTION, HORIZONTAL



MO340436



Connection, rear view

SCHRACK INFO


Basic unit without release, factory assembled with selected components and delivered as complete device.

DESCRIPTION	WEIGHT (kg)	I _{CU}	TYPE	ORDER NO.
3-POLE 100 kA				
4000 A	148	100 kA	MO3H-4000	MO340436
5000 A	148	100 kA	MO3H-5000	MO350436
6300 A	160	100 kA	MO3H-6300	MO363436
4-POLE 100 kA				
4000 A	190	100 kA	MO3H-4-4000	MO340446
5000 A	190	100 kA	MO3H-4-5000	MO350446
6300 A	227	100 kA	MO3H-4-6300	MO363446

FRAME SIZE 3 TO 6300A – WITH GUIDE FRAME, REAR-SIDE CONNECTION, VERTICAL



MO340437



Connection, rear view

SCHRACK INFO


Basic unit without release, factory assembled with selected components and delivered as complete device.

DESCRIPTION	WEIGHT (kg)	I _{CU}	TYPE	ORDER NO.
3-POLE 100 kA				
4000 A	148	100 kA	MO3H-4000	MO340437
5000 A	148	100 kA	MO3H-5000	MO350437
6300 A	166	100 kA	MO3H-6300	MO363437
4-POLE 100 kA				
4000 A	190	100 kA	MO3H-4-4000	MO340447
5000 A	190	100 kA	MO3H-4-5000	MO350447
6300 A	227	100 kA	MO3H-4-6300	MO363447

FRAME SIZE 3 TO 6300A – WITH GUIDE FRAME AND CONNECTING FLANGE



MO340436



Connection, rear view

SCHRACK INFO

Basic unit without release, factory assembled with selected components and delivered as complete device.

DESCRIPTION	WEIGHT (kg)	I _{CU}	TYPE	ORDER NO.
3-POLE 100 kA				
4000 A	148	100 kA	MO3H-4000	MO340438
4-POLE 100 kA				
4000 A	190	100 kA	MO3H-4-4000	MO340448